

Listing of Claims

1. (Cancelled).
2. (Cancelled).
3. (Cancelled).
4. (Cancelled).
5. (Cancelled).
6. (Cancelled).
7. (Cancelled).
8. (Cancelled).
9. (Cancelled).
10. (Cancelled).
11. (Cancelled).
12. (Cancelled).
13. (Cancelled).
14. (Cancelled).
15. (Cancelled).
16. (Cancelled).
17. (Cancelled).
18. (Cancelled).
19. (Cancelled).
20. (Cancelled).
21. (Previously Presented) A fuel additive composition intended to be used at a dose level of from about 20 to about 500ppm by weight in a liquid hydrocarbon fuel

combusted in internal combustion machines, said composition comprising, in admixture form:

- (a) from about 10 to about 57.2% by weight of water;
- (b) from about 28.9 to about 80% by weight of a surfactant wherein the surfactant is a combination of amine alkylbenzene sulphonate, POE (20) sorbitan monooleate, tall oil fatty acids, oleyl imidazoline hydrochloride and oleamide diethanolamine;
- (c) from about 0 to about 27.5% by weight of a co-surfactant selected from the group consisting of:
 - (i) low molecular weight alcohols
 - (ii) low molecular weight glycols
 - (iii) glycol ethers and
 - (iv) combinations of one or more of said (i) through (iii) co-surfactants;
- (d) from about 0 to about 30% by weight of a hydrocarbon solvent.

22. (Previously Presented) A micro-emulsion fuel composition intended to be combusted in internal combustion machines, said composition comprising:

- (a) from about 999,500 to about 999,980ppm by weight of a liquid hydrocarbon fuel;
- (b) from about 11 to about 400ppm by weight of a surfactant wherein the surfactant is a combination of amine alkylbenzene sulphonate, POE (20) sorbitan monooleate, tall oil fatty acids, oleyl imidazoline hydrochloride and oleamide diethanolamine

(c) from about 0 to about 100ppm by weight of a co-surfactant selected from the group consisting of:

- (i) low molecular weight alcohols
- (ii) low molecular weight glycols
- (iii) glycol ethers and
- (iv) combinations of one or more of said (i) through (iii) co-surfactants;

(d) from about 0 to about 150ppm by weight of a hydrocarbon solvent;

(e) from about 5 to about 95ppm by weight of added water, such that the weight ratio of said surfactant to said added water falls within the range of from about 8:1 to about 0.5:1.

23. (Previously Presented) A micro-emulsion fuel composition intended to be combusted in internal combustion machines, said composition comprising:

(a) from about 999,500 to about 999,980ppm by weight of a liquid hydrocarbon fuel;

(b) from about 11 to about 400ppm by weight of a surfactant selected from the group consisting of:

- (i) non-ionic
- (ii) anionic
- (iii) cationic
- (iv) amphoteric and
- (v) combinations of one or more of said (i) through (iv) surfactants;

(c) from about 21 to about 42ppm by weight of a co-surfactant selected from the group consisting of:

- (i) low molecular weight alcohols
 - (ii) low molecular weight glycols
 - (iii) glycol ethers and
 - (iv) combinations of one or more of said (i) through (iii) co-surfactants;
- (d) from about 0 to about 150ppm by weight of a hydrocarbon solvent;
- (e) from about 5 to about 95ppm by weight of added water, such that the weight ratio of said surfactant to said added water falls within the range of from about 8:1 to about 0.5:1.